			PUMP SPECIFICA	TION					
stomer Name:			Contact:			_	Date:		
			DATA FO	OR PRODUC	T TO BE PUMPED				
	Product Na	ame:							
	Viscosity (if not	water):		cps	Specific gravity (if not w	ater):			
	Size of solids if a	iny:			Product Temperature:	°F			
	%Chemical conc	entration (if not wa	ater):			°C 			
	PUI	VP PROCESS REQ	UIREMENT DA	rA]				
ODED SUCTION			-						
w rate:	gpm. lb/hr	Head:		ft psi	HEAD SIZE ID - INCHES N IMPELLER SIZE - INCHES				
tion size:	in	Inlet Fitting:	T	Choose one	SHAFT SEA			1	
			Tri-clamp Bevel seat	-	TYPE - E	EXTERNAL MECHANIC FACES	AL	-	
			Weld end FNPT Threaded		CASCADE FLUSH		. One	1	
			MNPT Threaded		FLUSH	SHAFT 0-RING	Choose one		
			Cam Lock		1		BUNA VITON		
let size:	in Fitting:	Outlet Fitting:	Tri-clamp	Choose one]		EPDM Silicone		
			Bevel seat Weld end		SHAFT SEA			1	
			FNPT Threaded		TYPE - IN				
			MNPT Threaded Cam Lock			FACES TE SHAFT 0-RING	FE/SS Choose one	-	
					┛				
							BUNA		
							VITON EPDM		
				DATA	, L		VITON	J	
			DRIVER	_	Chk. One		VITON EPDM Silicone		
		Electric Motor	DRIVER	<mark>DATA</mark> HP KW	Chk. One	Gas Engine Pow	VITON EPDM Silicone	HP CI	
		AC Frequency:	DRIVER	HP KW Hz	Chk. One	Gas Engine Spe	VITON EPDM Silicone ver:	НР	
			DRIVER	HP KW	Chk. One	Spe	VITON EPDM Silicone ver: ed: Chk. One	HP KW	
		AC Frequency: Speed	DRIVER	HP KW Hz		Spe	VITON EPDM Silicone ver: ed:	HP KW rpm	
		AC Frequency: Speed	DRIVER	HP KW Hz		Spe Model: GX_ Shaft Type	VITON EPDM Silicone ver: ed: Chk. One H	HP KW rpm	